

مترای موثر بعد از رینگ	دمای سیال	سرعت سیال	قدرت میدان	سختی کل آب مصرفی	طول دستگاه	قطر بیرونی	نوع اتصال	سایز
m 250	°C up to 90	m/s up to 3 m/s 0.1	6000gauss	800ppm	50	83	کلمپ	pts1/2
m 250	°C up to 90	m/s up to 3 m/s 0.1	6000gauss	800ppm	62	74/4	کلمپ	3/4in
250m	°C up to 90	m/s up to 3 m/s 0.1	6000gauss	800ppm	62	80/6	کلمپ	1in
250m	°C up to 90	m/s up to 3 m/s 0.1	6000gauss	800ppm	67	108	کلمپ	1 1/2in
500m	°C up to 90	m/s up to 4 m/s 0.1	7000gauss	800ppm	67	110	کلمپ	2in
500m	°C up to 90	m/s up to 4 m/s 0.1	7000gauss	800ppm	67	134	کلمپ	1 1/2in 2
600m	°C up to 90	m/s up to 3 m/s 0.1	8000gauss	800ppm	67	150	کلمپ	3in
800m	°C up to 90	m/s up to 4 m/s 0.1	8000gauss	800ppm	72	183	کلمپ	4in
800m	°C up to 90	m/s up to 4 m/s 0.1	8000gauss	800ppm	67	209	کلمپ	5in
1000m	°C up to 90	m/s up to 4 m/s 0.1	8000gauss	800ppm	72	301	کلمپ	6in
1000m	°C up to 90	m/s up to 4 m/s 0.1	8000gauss	800ppm	72	337	کلمپ	8in